



Performance Friction RH665 DOT 4 Racing Brake Fluid

IMPORTANT! HEALTH AND SAFETY INFORMATION

Product:	Performance Friction RH665 Dot 4 Racing Brake Fluid
Description:	Colourless to amber mobile liquid containing polyalkylene glycols and polyalklene glycol ethers.
Application	Competition Brake Fluid

FIRST AID PROCEDURES

Eyes	Eye contact will cause irritation. Flush immediately with copious quantities of water for at least 10 minutes. Obtain medical attention.
Skin	Wash well with soap and water. Repeated and prolonged contact may give rise to skin disorder. Should this develop, obtain medical advice.
Ingestion	If a substantial quantity is ingested, obtain medical attention immediately.
Aspiration	Obtain medical attention immediately.
Inhalation	In the unlikely event of inhalation, remove from Exposure and obtain medical attention

FIRE PROTECTION INFORMATION

Flash Point (test method)	145°C (Cleveland Open Cup) (NOT classified as highly flammable).
Suitable Extinuising Media	Any convenient means e.g. CO ₂ dry powder, foam or water.
Hazardous Decompostion / Combustion Products	Irritant fumes. Breathing apparatus must be worn.

IMPORTANT! HEALTH AND SAFETY INFORMATION

SAFETY HANDLING ADVICE

STORAGE

1. Avoid any contamination of this product by oil, petrol, solvents or water.
2. Store undercover in original sealed container.
3. Store below 50°C if possible to prevent pressurisation of container.

HANDLING

1. Wear eye protection, impervious gloves and apron when transferring between containers.
2. Change any contaminated clothing immediately.
3. This product has a defatting action on the skin. Prolonged exposure may give rise to skin disorders. Apply a suitable barrier cream before use, and emollient cream after use.
4. Do not eat, drink or smoke whilst using this product.
5. Leakage from high pressure systems may result in mist formation. Ensure adequate ventilation.

WARNING STATEMENT

No significant hazard when used in the application for which it was designed for. Harmful if swallowed in quantity. Mild eye and skin irritant.

OCCUPATIONAL EXPOSURE LIMITS - EH 40 LISTED

8 Hour TWA	10 Minute TWA
Not Listed	Not Listed

CONVEYANCE INFORMATION

UN / SI Number	Not classified as
Classification	dangerous for conveyance
Packing Group	by any means of transport
CEPIC Tremcard No.	nationally or
Hazchem Name	Internationally
ITATA / IACO	

SUPPLY INFORMATION

Classification: Xi-Irritant
Risk Phrases: R36 R52 R53
Safety Phrases: S2 S26 S29 S46

PROTECTION OF THE ENVIRONMENT

Behaviour in water	Miscible with water
Spillage	Prevent entry into drains, sewers and watercourses. Soak up with inert absorbent material.
Waste Disposal	Dispose of in can via an authorised contractor as oil-hazardous waste. EWC No. 16.01.13

Performance Friction (UK) Ltd

Carbon Metallic House, Wildmere Road, Banbury Oxon OX16 3LU United Kingdom
Tel: +44(0)1295 221020 Fax: +44(0)1295 279711

uksales@performancefriction.com
www.performancefriction.com