# SAFETY DATA SHEET



MEXICO: +52 55 5004 8763

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name: GEAR COMPETITION 75W140 12X1L

Product code: 105779

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Transmission oil

### 1.3. Details of the supplier of the safety data sheet

Registered company name: MOTUL

Address: 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE

Telephone: 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: .

Email: motul\_hse@motul.fr

### 1.4. Emergency telephone number: +44 (0) 1235 239 670.

Association/Organisation: . Other emergency numbers

UNITED STATES AND CANADA: 001 866 928 0789

BRAZIL: +55 11 3197 5891 CHILE: +562 2582 9336

### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

### In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

#### 2.2. Label elements

## In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :

EUH208 Contains OLEFIN SULFIDE. May produce an allergic reaction.
EUH208 Contains AMINE ALKYLE. May produce an allergic reaction.

## 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European

CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.2. Mixtures

### Composition:

Identification	(EC) 1272/2008	Note	%
CAS: 157707-86-3	GHS08		10 <= x % < 25
EC: 500-393-3	Dgr		
REACH: 01-2119493949-12-0000	Asp. Tox. 1, H304		
DEC-1-ENE, TRIMERS,			
HYDROGENATED			
CAS: 68937-96-2	GHS07		2.5 <= x % < 10
EC: 273-103-3	Wng		
REACH: 01-2119540515-43	Skin Sens. 1B, H317		
	Aquatic Chronic 3, H412		
OLEFIN SULFIDE			
EC: 931-384-6	GHS07, GHS05, GHS09		1 <= x % < 2.5
REACH: 01-2119493620-38	Dgr		
	Acute Tox. 4, H302		
AMINE ALKYLE	Skin Sens. 1, H317		
	Eye Dam. 1, H318		

	Aquatic Chronic 2, H411	
CAS: MIXTURE EC: MIXTURE	GHS08 Dgr	1 <= x % < 2.5
MINERAL OIL	Asp. Tox. 1, H304	
EC: 939-591-3 REACH: 01-2119978530-33	Aquatic Chronic 3, H412	1 <= x % < 2.5
REACTION PRODUCTS OF ALCOHOLS, C14-18, C18 UNSAT., ESTERIFIED		
WITH PHOSPHORUS PENTOXIDE AND SALTED WITH AMINES, C12-14,-TERT-ALKYL		

#### **SECTION 4: FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures

### In the event of exposure by inhalation:

In the event of an allergic reaction, seek medical attention.

Remove the victim to fresh air. If the symptoms persist, call a physician.

#### In the event of splashes or contact with eyes:

Wash immediately and abundantly with water, including under the eyelids.

### In the event of splashes or contact with skin:

In the event of an allergic reaction, seek medical attention.

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

### In the event of swallowing:

Seek medical attention, showing the label.

Rinse the mouth with water then drink a lot of water.

Do not induce vomiting without medical advice.

# 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## **SECTION 5: FIREFIGHTING MEASURES**

Non-flammable.

### 5.1. Extinguishing media

## Suitable methods of extinction

In the event of a fire, use:

- foam
- powder
- carbon dioxide (CO2)

## Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

### 5.3. Advice for firefighters

No data available.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Spilled product may make surfaces slippery.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

#### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

#### **SECTION 7: HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

#### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Avoid contact with eyes.

No special precaution apart from the observance of hygiene rules

Use only in well-ventilated areas.

#### Fire prevention:

Prevent access by unauthorised personnel.

Take precautionary measures against static discharges by bonding and grounding equipment.

No smoking.

### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Ensure good ventilation at the workplace

### Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

Do not breathe fumes, vapour, spray.

### 7.2. Conditions for safe storage, including any incompatibilities

Store between 5°C and 40°C in a dry, well ventilated place.

Only use hydrocarbon-resistant containers, joints and pipes.

Keep container tightly closed.

Storage life: 24 months.

### Storage

Keep out of reach of children.

### **Packaging**

Always keep in packaging made of an identical material to the original.

## 7.3. Specific end use(s)

No data available.

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### 8.1. Control parameters

No data available.

### 8.2. Exposure controls

## Personal protection measures, such as personal protective equipment



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

#### - Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of aloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties:

- Impervious gloves in accordance with standard EN374

### - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Face shield, boots, fluid-impermeable clothing, safety shoes, if needed.

#### - Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### 9.1. Information on basic physical and chemical properties

#### General information:

Physical state:

	10000
pH:	Not relevant.
Important health, safety and environmental information	
Color:	Blue
•	•

Fluid liquid.

pH:	Not relevant.
Flash Point Interval :	FP > 100°C.
Vapour pressure (50°C):	Below 110 kPa (1.10 bar).
Density:	<1
Water solubility:	Insoluble.
Viscosity:	168.6 mm²/s à 40°C

### 9.2. Other information

No data available.

### **SECTION 10: STABILITY AND REACTIVITY**

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

## 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Avoid :

- heat
- flames and hot surfaces

# 10.5. Incompatible materials

Keep away from:

- strong oxidising agents

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

## **SECTION 11: TOXICOLOGICAL INFORMATION**

### 11.1. Information on toxicological effects

No data available.

### 11.1.1. Substances

### Acute toxicity:

DEC-1-ENE, TRIMERS, HYDROGENATED (CAS: 157707-86-3)

Oral route: 2000 < LD50 <= 5000 mg/kg

Species: Rat

#### Germ cell mutagenicity:

AMINE ALKYLE

No mutagenic effect.

#### Reproductive toxicant:

AMINE ALKYLE

No toxic effect for reproduction

#### 11.1.2. Mixture

### Skin corrosion/skin irritation:

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

### Serious damage to eyes/eye irritation :

Mild eye irritation

### Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.

#### Aspiration hazard :

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons."

May cause lung damage if swallowed

## **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1. Toxicity

## 12.1.1. Substances

OLEFIN SULFIDE (CAS: 68937-96-2)

Crustacean toxicity: EC50 63 mg/l

Duration of exposure: 48 h

Algae toxicity: ECr50 > 100 mg/l

Duration of exposure: 72 h

Aquatic plant toxicity: Duration of exposure: 72 h

REACTION PRODUCTS OF ALCOHOLS, C14-18, C18 UNSAT., ESTERIFIED WITH PHOSPHORUS PENTOXIDE AND SALTED WITH AMINES,

C12-14,-TERT-ALKYL

Fish toxicity: LC50 > 1000 mg/l

Crustacean toxicity: EC50 = 91 mg/l

Duration of exposure: 48 h

Aquatic plant toxicity: ECr50 > 10 mg/l

Species : Others

Duration of exposure: 3 h

MINERAL OIL (CAS: MIXTURE)

Fish toxicity: LC50 > 100 mg/l

Species : Pimephales promelas Duration of exposure : 96 h

Crustacean toxicity: EC50 > 10000 mg/l

Duration of exposure: 48 h

NOEC > 10 mg/l

Duration of exposure: 21 jours

Algae toxicity: ECr50 > 100 mg/l

Species: Scenedesmus quadricauda

Duration of exposure: 72 h

AMINE ALKYLE

Fish toxicity: LC50 = 24 mg/l

Species: Others

Duration of exposure: 96 h

NOEC = 3.2 mg/l

Duration of exposure: 96 h

Crustacean toxicity: EC50 = 91.4 mg/l

Species: Others

Duration of exposure: 48 h

NOEC = 0.12 mg/l

Duration of exposure: 21 jours

Algae toxicity: ECr50 = 6.4 mg/l

Species: Selenastrum capricornutum

Duration of exposure: 96 h

NOEC = 1.7 mg/l

Species: Selenastrum capricornutum

Duration of exposure: 96 h

Aquatic plant toxicity: 1 < ECr50 <= 10 mg/l

Species : Others

DEC-1-ENE, TRIMERS, HYDROGENATED (CAS: 157707-86-3)

Fish toxicity: LC50 > 1000 mg/l

Duration of exposure: 96 h

Crustacean toxicity: EC50 > 1000 mg/l

Species : Daphnia magna Duration of exposure : 48 h

NOEC = 125 mg/l Species : Daphnia magna Duration of exposure : 21 jours

Algae toxicity: NOEC = 100 mg/l

Duration of exposure: 72 h

## 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

## 12.2.1. Substances

REACTION PRODUCTS OF ALCOHOLS, C14-18, C18 UNSAT., ESTERIFIED WITH PHOSPHORUS PENTOXIDE AND SALTED WITH AMINES,

C12-14,-TERT-ALKYL

Biodegradability: no degradability data is available, the substance is considered as not

degrading quickly.

MINERAL OIL (CAS: MIXTURE)

Biodegradability: no degradability data is available, the substance is considered as not

degrading quickly.

AMINE ALKYLE

GEAR COMPETITION 75W140 12X1L - 105779

no degradability data is available, the substance is considered as not

degrading quickly.

OLEFIN SULFIDE (CAS: 68937-96-2)

Biodegradability: no degradability data is available, the substance is considered as not

degrading quickly.

DEC-1-ENE, TRIMERS, HYDROGENATED (CAS: 157707-86-3)

Biodegradability: Non-rapidly degradable.

### 12.3. Bioaccumulative potential

#### 12.3.1. Substances

Biodegradability:

DEC-1-ENE, TRIMERS, HYDROGENATED (CAS: 157707-86-3) Bioaccumulation: BCF > 10

REACTION PRODUCTS OF ALCOHOLS, C14-18, C18 UNSAT., ESTERIFIED WITH PHOSPHORUS PENTOXIDE AND SALTED WITH AMINES,

C12-14,-TERT-ALKYL

Octanol/water partition coefficient : log Koe = 8

OLEFIN SULFIDE (CAS: 68937-96-2)

Octanol/water partition coefficient : log Koe = 6

#### 12.4. Mobility in soil

Not very mobile in soil.

The product is insoluble in water and will spread on the surface

#### 12.5. Results of PBT and vPvB assessment

No data available.

### 12.6. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.

### German regulations concerning the classification of hazards for water (WGK) :

WGK 1 (VwVwS vom 27/07/2005, KBws): Slightly hazardous for water.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

## Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste):

13 02 06 \* synthetic engine, gear and lubricating oils

## **SECTION 14: TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

### 14.1. UN number

## 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

# 14.4. Packing group

## 14.5. Environmental hazards

### 14.6. Special precautions for user

-

### **SECTION 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

- Container information:

No data available.

- Particular provisions :


No data available.

- German regulations concerning the classification of hazards for water (WGK) :

WGK 1 (VwVwS vom 27/07/2005, KBws): Slightly hazardous for water.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704):

NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



### 15.2. Chemical safety assessment

Product is not classified health and environmental hazard. Exposure scenarios are not required.

## **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

### Wording of the phrases mentioned in section 3:

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

## Abbreviations :

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.