

PCRS

Gonesse, le 02/03/2020.

INFO-TECH CITROËN Racing C3R5 20-08


Sujet : Jauge à essence (904477528A)




Afin d'éviter de blesser le fond de l'outre avec l'extrémité de la jauge, nous vous recommandons d'ajouter un point de colle (Araldite AW2101 - HW2951) à son extrémité.



Merci de garder un gap (mini) de 1mm entre l'extrémité de la jauge et l'outre. Vous pouvez ajuster ce gap via des joints cuivre (PS81052A10).



Minimum 1 copper washer for sealing. Add 1 or more washer to adjust the fuel gauge gap.



Gap = 1mm min

Nous vous conseillons ensuite de procéder à un nouvel étalonnage du réservoir suite à ce repositionnement de jauge.

L'équipe du support technique,

Damien Arbonnier
damien.arbonnier@mpsa.com
 Mobile : +33 6 74 56 77 86

Christophe Vely
christophe.vely@mpsa.com
 Mobile : +33 7 61 51 37 92


Subject: Fuel gauge (904477528A)




To avoid hurting the fuel cell with the extremity of the fuel gauge, we advise you to add some glue (Araldite AW2101 - HW2951) to the end of the gauge.



Please keep a gap of 1mm (min) between the fuel cell and the fuel gauge extremity by adjusting with copper washers (PS81052A10).



Minimum 1 copper washer for sealing. Add 1 or more washer to adjust the fuel gauge gap.



We recommend you to proceed a new fuel sampling following this gauge repositioning.

The technical support team,

Damien Arbonnier
damien.arbonnier@mpsa.com
 Mobile : +33 6 74 56 77 86

Christophe Vely
christophe.vely@mpsa.com
 Mobile : +33 7 61 51 37 92