

SALES INFORMATION



Technical data

Engine

Type: EP6C (special pistons, con-rods, camshafts).

Cubic capacity: 1.598cc

Bore x stroke: 77mm x 85.8mm

Maximum power: 185hp at 7.800rpm

Maximum torque: 19m.daN at 6.300rpm

Specific power: 116hp/litre Fuel tank: 60 litres

Fuel injection: Indirect (Magneti-Marelli), motorized single throttle valve,
Chain-driven Double overhead camshafts with VVT intake and exhaust timing

Gearbox

Gearbox: Five-speed sequential manual gearbox with three homologated final drive ratios

Differential: Pre-loaded limited slip differential

Clutch: Hydraulically operated cerametallic single clutch plate (diameter: 184mm)

Brakes/Steering

Front brakes: Ventilated discs and radial-mount four-piston floating-calipers

- asphalt: 310mm x 30mm (diameter x thickness)- gravel: 285mm x 26mm (diameter x thickness)

Rear brakes: Solid discs: 290mm x 8mm (diameter x thickness) and radial-mount two-piston

calipers

Handbrake: Hydraulic Power steering: Hydraulic

Suspension

Front: MacPherson type with specific uniball-jointed wishbones

Specific interchangeable front anti-roll bar (3 stiffnesses choices) with plain

bearings

Specific cast aluminium struts (camber adjustment at pivot).

Rear: Strengthened H-beam modified to fit an interchangeable anti-rollbar (choice of 3

stiffnesses)

Front/rear dampers: Specific three-way Öhlins dampers with adjustable hydraulic bump stops

Chassis

Structure: Bodyshell reinforced by welded, multipoint FIA-approved rollcage specific steel

& underbody shielding

Weight: Minimum weight (FIA regulations): 1.030kg (unladen), and 1.180kg (with crew)

Front/rear distribution: 64% / 36%

Dimensions

Length/width: 3.962mm / 1.739mm

Wheelbase: 2.538mm

Front/rear track: 1.475mm / 1.470mm

Wheels

Wheels/tyres: Asphalt - wheels: 6.5 x 16 / Michelin Pilot Sport tyres (19/60-16)

Gravel - wheels: 6 x 15 / Michelin tyres (16/64-15)