



## FIRE SUPPRESSION

### SALES DATA SHEET

Electrically Activated Plumbed-In 2.7kg Coldfire Extinguisher

Model Number: CF-TEC2700EK

FIA - TECHNICAL LIST 52



#### Installation Kit Contents

- 1 x 2-Part End Bracket
- 2 x Standard nut & bolt strap (526mm)
- 1 x Electrical control unit – Binder
- 1 x EK Electrical control unit loom – Binder
- 1 x External fire button & fly lead
- 1 x Internal fire button with metal shroud
- 5.5 mtr of 10mm Aluminium pipework
- 2.0 mtr of 6mm Aluminium pipework
- 1 x CF-TEC2700 Cockpit roll cage nozzle assembly
- 1 x CF-TEC2700 Footwell nozzle assembly
- 2 x CF-TEC2700 LH/RH engine nozzle with 6mm swivel elbow connector
- 1 x CF-TEC2700 Centre engine nozzle with 6mm Swivel T connector
- 1 x 6mm T connector
- 1 x 10mm Y connector
- 1 x 10mm Y connector with 6mm reducer installed
- 10 x 10mm Pipe Clips
- 5 x 6mm Pipe Clips
- 2 x Large E Decal, 1 x Small E Label
- 1 x Installation Instructions

|                                             |                    |
|---------------------------------------------|--------------------|
| <b>Part Number</b>                          | 100.000.210        |
| <b>Capacity</b>                             | 2.700kg            |
| <b>Complete Bottle Weight</b>               | 3.950kg            |
| <b>Weight Including Cradle &amp; Straps</b> | 4.350kg            |
| <b>Complete System with Kit Weight</b>      | 5.585kg            |
| <b>Activated</b>                            | Electrical         |
| <b>Pressure</b>                             | Pressurised 14 bar |
| <b>Cylinder</b>                             | Aluminium          |

**Note this system is for –**

**Class I - Petrol in accordance with Art.9 of Article 252 of the 2014 Appendix J**

**Class II - Petrol + up to 30% ethanol**

**Class V - E85**



**FIRE SUPPRESSION**  
**CF-TEC2700EK Dimensions**

