



FIRE SUPPRESSION

SALES DATA SHEET

Mechanically Activated Plumbed-In 2.7kg Coldfire Extinguisher

Model Number: CF-TEC2700MK

FIA - TECHNICAL LIST 52



Installation Kit Contents:

- 1 x 2-Part End Bracket
- 2 x Standard nut & bolt strap (526mm)
- 5.5 mtr of 10mm Aluminium pipework
- 2.0 mtr of 6mm Aluminium pipework
- 1 x 6ft T handle pull cable
- 1 or 2 x 12ft T handle pull cable
- 1 x CF-TEC2700 Cockpit roll cage nozzle assembly
- 1 x CF-TEC2700 Footwell nozzle assembly
- 2 x CF-TEC2700 LH/RH engine nozzle with 6mm swivel elbow connector
- 1 x CF-TEC2700 Centre engine nozzle with 6mm Swivel T connector
- 1 x 6mm T connector
- 1 x 10mm Y connector
- 1 x 10mm Y connector with 6mm reducer installed
- 10 x 10mm Pipe Clips
- 5 x 6mm Pipe Clips
- 5.5 mtr of 10mm Aluminium tubing
- 2.0 mtr of 6mm Aluminium tubing
- 2 x Large E Decal, 1 x Small E Label
- 1 x Installation Instructions

Note this system is for –

**Class I - Petrol in accordance with
Art.9 of Article 252 of the 2014
Appendix J**

Class II - Petrol + up to 30% ethanol

Class V - E85

Part Number	100.000.220
Capacity	2.700kg
Complete Bottle Weight	4.000kg
Weight Including Cradle & Straps	4.400kg
Complete System with Kit Weight	6.015kg
Activated	Mechanical
Pressure	Pressurised 14bar
Cylinder	Aluminium



FIRE SUPPRESSION
CF-TEC2700MK Dimensions

