

|                                    | unit.      | FRONT    |       | REAR     |       | <b>Comments:</b>             |
|------------------------------------|------------|----------|-------|----------|-------|------------------------------|
|                                    |            | Left     | Right | Left     | Right |                              |
| <b>TYRES</b>                       | Dimensions | 19/63-17 |       | 19/63-17 |       | Reference = Michelin         |
| <b>TYRE PRESSURE</b><br>for set up | bar        | 2.0      |       | 2.0      |       | New tyres for RH's reference |

G  
E  
O  
M  
E  
T  
R  
Y

|                                                                                                                                                                                                                                                                                   |    |               |       |             |       |                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---------------|-------|-------------|-------|-------------------------------------------------------------|
| RIDE HEIGHT (RH)                                                                                                                                                                                                                                                                  | mm | 245           |       | 410         |       | RH's Target recommended<br>(Measurement points end of page) |
| Theoretical cup heights (CH)                                                                                                                                                                                                                                                      | mm | 120 ≤ x ≤ 125 |       | 65 ≤ x ≤ 70 |       |                                                             |
| FRONT: 6 cup height rotation = 10mm of RH<br>REAR: 5 cup height rotation = 10mm of RH                                                                                                                                                                                             |    |               |       |             |       |                                                             |
| CAMBER                                                                                                                                                                                                                                                                            | °  | -1°45         | -1°45 | -1°35       | -1°35 | * Thickness may vary from<br>vehicle to an other            |
| Theoretical camber shims *                                                                                                                                                                                                                                                        | mm | 7,0           | 7,0   | 7           | 7     |                                                             |
| FRONT: 0.1mm of shim = 0°07' to the wheel<br>REAR: 1 shim step = 0°07' to the wheel                                                                                                                                                                                               |    |               |       |             |       |                                                             |
| TOE                                                                                                                                                                                                                                                                               | mm | 0,0           | 0,0   | 0,0         | 0,0   | * Thickness may vary from<br>vehicle to an other            |
| Theoretical TOE Shims *                                                                                                                                                                                                                                                           | N° |               |       | C           | C     |                                                             |
| FRONT: 1/2 of rod rotation = 0.75mm of Rod length = 2.0mm toe to the wheel.<br>Camber/Toe incidence: -0°30' of camber variation = +2.0mm toe to the wheel.<br>REAR: 1 Shim step = 1mm to the wheel<br>Camber/Toe incidence: -0°07' of camber variation = -0.4 mm toe at the wheel |    |               |       |             |       |                                                             |
| Wheelbase                                                                                                                                                                                                                                                                         | mm | 2553 (+/-10)  |       |             |       | Homologated value                                           |

S  
U  
S  
P  
E  
N  
S  
I  
O  
N

|                                                                                                                  |             |          |      |           |      |                                                         |    |    |    |     |
|------------------------------------------------------------------------------------------------------------------|-------------|----------|------|-----------|------|---------------------------------------------------------|----|----|----|-----|
| Minimum weight                                                                                                   | Kg          | W/o crew | 1080 | With Crew | 1240 | Category RC4 values<br><br>Low position = Mandatory     |    |    |    |     |
| WHISHBONE                                                                                                        | E1 Position | Low      |      |           |      |                                                         |    |    |    |     |
| MAIN SPRINGS                                                                                                     | N/mm        | 45       |      | 40,5      |      | Fully screw<br>out of the number of<br>clicks indicated |    |    |    |     |
| Helper springs                                                                                                   | N/mm        | 5        |      | 5         |      |                                                         |    |    |    |     |
| DAMPERS<br>Setting ( clicks )                                                                                    | Version     | FT011    |      | RT022     |      |                                                         |    |    |    |     |
|                                                                                                                  | Ways        | c        | C    | R         | PDS  |                                                         | c  | C  | R  | PDS |
|                                                                                                                  | Clicks      | 30       | 38   | 32        | 2    |                                                         | 15 | 28 | 20 | 2   |
| c= low speed compression / C= high speed compression / R= Rebound/ PDS= Progressive damping System ( hydraulic ) |             |          |      |           |      |                                                         |    |    |    |     |
| ANTIROLL BAR                                                                                                     | mm          | Ø        | 15   |           | Ø    | 22                                                      |    |    |    |     |
| ARB rod length                                                                                                   | mm          |          | 80   |           |      | 80                                                      |    |    |    |     |

|                                  |                            |    |      |      |                                      |
|----------------------------------|----------------------------|----|------|------|--------------------------------------|
| <b>S<br/>T<br/>E<br/>E<br/>R</b> | Steering rack height       | mm | 10,0 | 10,0 | Recommended default<br>Shims heights |
|                                  | <b>M-POINT SPACER (HA)</b> | mm | 5,0  | 5,0  |                                      |
|                                  | <b>M-POINT SPACER (BA)</b> | mm | 1,0  | 1,0  |                                      |
|                                  | Steering Pump nozzle       | mm | Ø    | 4 mm |                                      |

|                            |                      |             |              |   |            |
|----------------------------|----------------------|-------------|--------------|---|------------|
| B<br>R<br>A<br>K<br>E<br>S | Main master cylinder | mm          | Ø 22,22      |   |            |
|                            | BRAKE PADS           | Brand/model | Mintex / F4R |   | TM / Mix 2 |
|                            | BRAKE BALANCE        | bar         | 30           |   | 16         |
|                            | Handbrake MC         | mm          |              | Ø | 15mm       |

|                                  |                     |                |       |           |       |         |         |             |
|----------------------------------|---------------------|----------------|-------|-----------|-------|---------|---------|-------------|
| <b>T<br/>R<br/>A<br/>N<br/>S</b> | Gearbox Ratio       | Gears          | 1     | 2         | 3     | 4       | 5       | Final drive |
|                                  |                     | EVO Ratio      | 12x29 | 17x31     | 17x25 | 22x26   | 21x20   | 12x54       |
|                                  | <b>DIFFERENTIAL</b> | Friction Faces | 12 F  | Ramps (°) | 27/57 | Preload | 120 N.m | Hot         |

|                       |                 |                        |              |            |                      |
|-----------------------|-----------------|------------------------|--------------|------------|----------------------|
| F<br>L<br>U<br>I<br>D | Recommendations | Type                   | Reference    | Volume     |                      |
|                       |                 | Engine Oil :           | 0 W 30       | PS97727A10 | 3.5 L (+1.5 L radia) |
|                       |                 | GearBox Oil :          | 75 W 140     | 904895438A | 1 L (+0.1 L radia)   |
|                       |                 | Steering Fluid :       | LDS          | 1615099680 | 2 L                  |
|                       |                 | Coolant :              | PSA -35°C    | 1637756480 | 6.5 L                |
|                       |                 | Brake / Clutch Fluid : | BREMBO HTC64 | PS97633A10 |                      |

