



FIRE SUPPRESSION

SALES DATA SHEET

Electrically Activated Plumbed-In 2.7kg Coldfire Extinguisher

Model Number: CF-TEC2700EK

FIA - TECHNICAL LIST 52



Installation Kit Contents

- 1 x 2-Part End Bracket
- 2 x Standard nut & bolt strap (526mm)
- 1 x Electrical control unit – Binder
- 1 x EK Electrical control unit loom – Binder
- 1 x External fire button & fly lead
- 1 x Internal fire button with metal shroud
- 5.5 mtr of 10mm Aluminium pipework
- 2.0 mtr of 6mm Aluminium pipework
- 1 x CF-TEC2700 Cockpit roll cage nozzle assembly
- 1 x CF-TEC2700 Footwell nozzle assembly
- 2 x CF-TEC2700 LH/RH engine nozzle with 6mm swivel elbow connector
- 1 x CF-TEC2700 Centre engine nozzle with 6mm Swivel T connector
- 1 x 6mm T connector
- 1 x 10mm Y connector
- 1 x 10mm Y connector with 6mm reducer installed
- 10 x 10mm Pipe Clips
- 5 x 6mm Pipe Clips
- 2 x Large E Decal, 1 x Small E Label
- 1 x Installation Instructions

Part Number	100.000.210
Capacity	2.700kg
Complete Bottle Weight	3.950kg
Weight Including Cradle & Straps	4.350kg
Complete System with Kit Weight	5.585kg
Activated	Electrical
Pressure	Pressurised 14 bar
Cylinder	Aluminium

Note this system is for –

Class I - Petrol in accordance with Art.9 of Article 252 of the 2014 Appendix J

Class II - Petrol + up to 30% ethanol

Class V - E85



FIRE SUPPRESSION
CF-TEC2700EK Dimensions

